



DECLARATION OF PERFORMANCE

Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

BETEC® 300 HOZ

Nr.: DEYS-121399-03

Unique identification code of the product-type:

EN 1504-3: ZA.1a

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch No. see packaging of the product

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Product for structural and non structural repair of concrete
Applying mortar by hand (3.1)
Recasting with concrete (3.2)

PCC Mortar for non structural repair of concrete
(on the basis of hydraulic cement)

Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Deys Betontechniek BV
Gelreweg 5
3843 AN Harderwijk
Netherlands

Fabriek 1

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+, 4

Harmonised standard:

EN 1504-3:2005



Notified body/ies:

**The notified body QDB, identification number 0921, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued:
Certificate of conformity of the factory production control
0921-CPR-2120**

The classification of fire performance on the system 4 based on the composition in accordance with Decision 96/603/EC.

Declared performance

| Essential* Characteristics | Performance | System of assessment and verification of constancy of performance | Harmonised Technical Specification |
|----------------------------------|-------------|---|------------------------------------|
| Compressive strength | class R2 | System 2+ | EN 1504-3:2005 |
| Chloride ion content | ≤ 0,05 % | | |
| Adhesive bond | ≥ 0,8 MPa | | |
| Restrained shrinkage/expansion | ≥ 0,8 MPa | | |
| Carbonation resistance | NPD | | |
| Elastic modulus | ≥ 10 GPa | | |
| Thermal compatibility | NPD | | |
| Skid Resistance | NPD | | |
| Coefficient of thermal expansion | NPD | | |
| Capillary absorption | NPD | | |
| Reaction to fire | class E | System 4 | |
| Dangerous substances | NPD | System 2+ | |

NPD: No Performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: S. Deys Harderwijk 08-11-2018