



## DECLARATION OF PERFORMANCE

Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

**BETEC® Flex**

**Nr.: DEYS-112583-03**

Unique identification code of the product-type:

**EN 1504-2: ZA.1e**

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Batch No. see packaging of the product**

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Surface protection products – Coating  
Moisture control (2.2)**

Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Deys Betontechniek BV  
Gelreweg 5  
3843 AN Harderwijk  
Netherlands**

**Plant 1**

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 2+, 3**

Harmonised standard:

**EN 1504-2:2004**

Notified body/ies:

The notified body QDB, identification number 0921, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued:  
**Certificate of conformity of the factory production control  
0921-CPR-2063**

The notified body MPA NRW, identification number 0432, performed the determination of reaction to fire class on the basis of type testing under system 3 and issued:  
**test report 230007892-2**

Declared performance

Essential* Characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical Specification
Linear shrinkage	NPD	System 2+	<b>EN 1504-2:2004</b>
Coefficient of thermal expansion	NPD		
Cross cut	NPD		
Water vapour permeability	class 1		
Capillary absorption and permeability to water	< 0,1 kg/(m <sup>2</sup> * h <sup>0,5</sup> )		
Thermal compatibility	NPD		
Crack bridging ability	NPD		
Adhesion strength by pull off test	≥ 0,8 N/mm <sup>2</sup>		
Reaction to fire	class A2	System 3	
Skid resistance	NPD	System 2+	
Artificial weathering	NPD		
Antistatic behaviour	NPD		
Adhesion on wet concrete	NPD		
Release of dangerous substances	NPD		

NPD: No Performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: S.Deys, 19-02-2019